

W707 Kleen G

Concentrated Gel Detergent

High-viscosity concentrated gel detergent with alkaline pH, suitable for cleaning and removal of epoxy residues in all types of mosaic, tile, or natural stone, regardless of its porosity. Ideal for cleaning tough dirt residues on floors and walls.

USES

- For removing stains and residues left by epoxy grouts, such as W705 Epoxy Color 2K.
- For removal of stains on polished porcelain stoneware left behind by previous dark colored cementitious grouts
- Can be used as a de-greasing alkaline detergent: effective in removing greasy residues, organic dirt deposits accumulated over time and wax from all natural or artificial surfaces (with a recommended dilution rate of 30% with water).
- For deep cleaning of porous materials (with a recommended dilution rate of 30% with water).
- For periodic deep cleaning of all types of surfaces characterized by intense dirt, which cannot be removed using commonly sold detergents.
- Can be used as detergent to clean resilient flooring, such as PVC and linoleum.
- Can also be used as a universal detergent for hard surfaces, with proven efficacy in the removal of grease and organic deposits.

LIMITATIONS

- Use only within the recommended temperature range: 40 to 95°F (4 to 35°C).
- Doors, windows, rubber gaskets, furniture, taps and fittings, metal or PVC profiles and all surfaces that may be damaged by direct contact with the detergents should be protected prior use.
- Do not use the products for applications not specified in this Technical Data Sheet.

TECHNICAL DATA

Product Performance Properties at 73°F (23°C) and 50% relative humidity	
Specific Gravity	1010 ± 10 g/L
pH	12 ± 0.5
Appearance	Clear Highly Viscous Liquid
Odor	Peach-Like
Shelf Life	24 months
Application Temperature	40°F - 95°F
Application Time	10 - 15 minutes

PACKAGING

Product Code	Pack	Yield (Consumption Rate)
WE0770601	750 ML	10-15 m2/L

*Coverage depends on substrate conditions.

SURFACE PREPARATION

For the removal of epoxy grout stains or residue on newly installed surfaces, the detergents must be applied once the grouting has sufficiently hardened (normally after 24 hours at a temperature of 68°F - 77°F (20°C - 25°C)).

APPLICATION

1. Shake well before use.
2. Apply the undiluted product, spreading or spraying directly onto the surface.
3. Let detergent act for approximately 10-15 minutes.
4. Rub the surface with a white felt, such as W-705 Scotchbrite Fine White Pad, or using a polishing machine with a white pad for larger surfaces.
5. Collect the cleaning solution using a sponge, rubber squeegee broom or wet vacuum cleaner.
6. Finally, rinse well with clean water and dry with a clean rag or cloth. Do not wait for the rinse water to evaporate as this may cause stains to reappear on the surface.

SAFETY

Please refer to the Safety Data Sheet (SDS) for safety data. KEEP OUT OF THE REACH OF CHILDREN.

LEGAL DISCLAIMER

Before applying this product, customer must read the product information in this Technical Data Sheet to determine its suitability for the intended application. This product warranty is limited to its replacement or its refund value should it not comply with the specifications of the manufacturer and does not include any application costs. Customer must present original proof of purchase and submit claim in writing within 15 days from the alleged situation. The information in the Technical Data Sheet supersedes any other product information available from packaging and any other company or marketing documentation. Visit our website at www.wecopr.com for the most up-to-date official TDS.